



MATERIAL SAFETY DATA SHEET

Section 1: IDENTIFICATION

MASTER STRIP

Recommended Use: Floor polish stripper.
Product Code: 850



MASTER AUSTRALIA PTY LTD (A.B.N. 66 092 483 880)
Postal Address: 45 Marrickville Rd, Marrickville, NSW 2204
Telephone Number: (02) 9550 5800 Facsimile: (02) 9550 5876
Emergency Telephone Number: Poisons Information Centre (National) 13 11 26

Section 2: HAZARDS IDENTIFICATION

Classified as hazardous by the criteria of NOHSC.

Harmful.

R20/21/22: Harmful by inhalation, in contact with skin and if swallowed.

R34: Causes burns.

R37: Irritating to respiratory system.

S13: Keep away from food, drink and animal foodstuffs.

S24/25: Avoid contact with skin and eyes.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S37/39: Wear suitable gloves and eye/face protection when mixing or using.

S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label whenever possible.)

Section 3: COMPOSITION INFORMATION

<u>Ingredient</u>	<u>CAS No</u>	<u>Proportion</u>
Non-hazardous ingredients	-----	To 100%
Butyl glycol	111-76-2	10-30%
Potassium hydroxide*	1310-58-3	<10%

* actual concentration less than 5%.

Section 4: FIRST AID MEASURES

Eye (Contact)	Hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by the Poisons Information Centre, or for at least 15 minutes.
Skin (Contact)	Remove contaminated clothing and flush skin and hair with running water.
Inhalation(Breathing)	Apply artificial respiration if not breathing.

Ingestion (Swallowing) Do NOT induce vomiting. For advice, contact a Poisons Information Centre (Phone 131126) or a doctor.

Advice to Doctor Treat symptomatically.

Section 5: FIRE FIGHTING MEASURES

Suitable extinguishing media Use water spray, foam, carbon dioxide or dry chemical powder. Use media / equipment appropriate to surrounding fire conditions.

Hazards from combustion products Carbon dioxide and / or carbon monoxide.

Precautions for fire fighters and special protective equipment Firefighters must wear full protective clothing including self contained breathing apparatus and chemical splash suit. Ensure that no spillage enters drains or water courses. Remove from the vicinity containers not involved in the fire.

Additional information Hazchem Code – 2R

Section 6: ACCIDENTAL RELEASE MEASURES

Emergency procedures SAA/SNZ HB76: Dangerous Goods – Initial Emergency Response Guide – Guide 37.

Methods and materials for containment and clean up Clear area of all unprotected personnel. Wear full protective equipment to prevent skin and eye contact. Ventilate area of leak or spill. Collect in an appropriate container or absorb with an inert material (eg vermiculite, dry sand, earth), and place in a chemical waste container. Do not use combustible products like saw dust.

Section 7: HANDLING AND STORAGE

Precautions for safe handling Any non-intended or non-authorized use of this product may result in severe personal injury or damage to equipment. Store product in original container. Wash hands and face thoroughly after handling and before work breaks, eating, drinking, smoking and using toilet facilities.

Conditions for safe storage, including any incompatibilities Store in a cool, dry, well ventilated area away from incompatible materials. Keep container tightly sealed. Check regularly for spills and leaks. Protect against physical damage.

Section 8: EXPOSURE CONTROL/PERSONAL PROTECTION

National Exposure Standards - Source: National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003].

<u>Ingredient</u>	<u>CAS No</u>	<u>TWA</u>	<u>STEL</u>
Butyl glycol	111-76-2	20ppm 96.9mg/m ³	50ppm 242mg/m ³

Biological limit values Not available.

Engineering controls Ensure adequate ventilation to keep airborne concentrations below exposure standards.

Personal protective equipment

Eye/face protection – Safety glasses or chemical resistant goggles should be worn to prevent eye contact.

Skin protection – Use impervious gloves, overalls, apron and chemical resistant shoes to prevent skin contact.

Respiratory protection – Respirator is not usually necessary but if product is being used in a confined area or where vapour/mist is a problem, use a respirator with inorganic vapour filter.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Clear thin liquid	Boiling Point:	Approximately 100°C
Odour:	Characteristic	Freezing Point:	Approximately 0°C
pH:	13 - 14	Solubility:	Soluble in water.
Vapour Pressure:	Not applicable	Specific Gravity:	1.01
Vapour Density:	Not applicable	Flammable information:	Not applicable

Section 10: STABILITY AND REACTIVITY

Chemical stability	Stable under normal ambient storage conditions.
Conditions to avoid	Avoid high temperatures (store below 30°C). Protect against physical damage.
Incompatible materials	None known.
Hazardous decomposition products	None known.
Hazardous reactions	None known.

Section 11: TOXICOLOGICAL INFORMATION

HEALTH EFFECTS**Acute**

Swallowed Considered an unlikely route of entry in commercial / industrial environments. May be corrosive to mucous membranes and may cause damage to esophagus and stomach. Abdominal pain, nausea, vomiting, general gastrointestinal upset can be expected.

Eye May cause tearing, redness and pain. Contamination of eyes can result permanent injury and possible loss of eye sight.

Skin May cause pain irritation and reddening.

Inhaled Inhalation of mist or aerosols may result in respiratory irritation and possible harmful effects.

Chronic

Swallowed No effects known.

Eye No effects known.

Skin No effects known.

Inhalation No effects known.

TOXICITY DATA

Potassium hydroxide	LD ₅₀ 273mg/kg (oral, rat)	RTECS TT2100000
Butyl glycol	LD ₅₀ 1230mg/kg (oral, mouse)	RTECS KJ8575000

Section 12: ECOLOGICAL INFORMATION

Not expected to be ecotoxic.
Biodegradability data not yet available.

Section 13: DISPOSAL CONSIDERATIONS

Refer to state/Territory Land Waste Management Authority. Dispose of material through a licensed waste contractor. Normally suitable for incineration by approved agent.

Section 14: TRANSPORT INFORMATION

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code).

UN Number	1719
UN Proper Shipping Name	CAUSTIC ALKALI LIQUID, N.O.S.
Class and subsidiary risk	8 – Corrosive
Packing Group	II
Special precautions for user	Not applicable
Hazchem Code	2R

Section 15: REGULATORY INFORMATION

Poisons Schedule (SUSDP): Schedule 5 – CAUTION.

WARNING: Corrosive. May produce severe burns. Attacks skin and eyes.

SAFETY: Wear eye protection when mixing or using. Wear protective gloves when mixing or using.

All ingredients are listed on the Australian Inventory of Chemical Substances (AICS).

Section 16: OTHER INFORMATION

Prepared by: K. Duncum

Position: Regulatory Compliance Technician

Date: 9 December 2005

© This document remains property of *Master Australia Pty Ltd.*
Alterations are not permitted without prior written authorisation
from *Master Australia Pty Ltd.*